### SHAW MACHINERY 12 FILMER STREET

4019 Ph: 0738832731 Fx: 0738832732 E: sales@shawmachinery.com.au



# S829 MetalMaster Cold Saw, Includes Stand CS-350V





 Code:
 S829

 Model:
 CS-350V

 Capacity:
 160 x 90mm

 Weight (Nett):
 280

 Dimensions:
 119 x 72 x 160

#### Description

The latest 240 volt Hafco MetalMaster manual cold saw consists of a 350mm circular saw blade that can run at 24 to 120rpm via a electronic variable blade speed control and also incorporates a coolant system with an adjustable flow control valve. These cold saws are designed to cut at 90Ű, or mitre up to 45Ű in either left or right side of the material simply by releasing the lever located at front of machine and swivelling the head to the desired angle. Each machine comes standard with a very heavy and strong cast iron frame base with a cast dual pivot saw head supported by an industrial swivel base system, which makes this MetalMaster cold saw one of the most rugged machines on the market.

The MetalMaster manual cold saw head is well balanced and uses a long actuating handle giving the operator greater leverage and control to guide the saw blade through the work piece of tubing or pipe etc, with ease and utilises a quality head retraction system for returning the cold saw head to the start position. The vice clamps the work piece on both sides of a cut, which extends blade life because the cut off does not drop into the blade.

#### Features

- Electronic variable speed 24~120rpm
- 2.2kW / 3hp 240V heavy duty motor
- Rugged cast iron construction offers years of accurate cutting
- Lock at any angle between -45° or +45° mitre in both directions via locking lever
- Degree markings engraved onto swivelling base for quick and accurate mitre cutting
- Dual material clamp system providing burr free cuts on both pieces of material
- Quick action vice clamp lever designed to increase production
- Built in blade coolant pump system with flow control valve

- Oil sight glass located on right side of the gearbox so operator can maintain correct lubrication levels according to specifications provided

- Dead man trigger switch located on cutting handle provides operator safety on/off power control
- Automatic retract safety blade guard covers blade when returned to home position



- Spring assisted head return provides a even balance during cutting operation and reduces operator fatigue
- HSS cutting blade is included for general types of material and thickness

#### Includes

- Blade
- Coolant system
- Stand

## **Specifications**

CODE	S829
Model	CS-350V
Cutting Head Action (auto-manual)	Manual
Operation Type	Swivel - Dual Mitre
Round Capacity @ 90º / 45º	120mm / 100mm
Square Capacity @ 90º / 45º	105mm / 85mm
Rectangle Capacity @ 90º / 45º	160 x 90mm / 85 x 70mm
Blade Size (Ã~ X Bore)	350 x 32mm
Vice Clamping Fixture	Manual

Coolant System	Yes
Table Working Height (with Stand)	1000mm
Blade Speeds	24 - 120rpm
Motor Power	2.2kW / 3hp
Voltage	240V - 20amp
Weight (nett)	250kg

