

OPTIMUM TU-3008G

OPTIMUM[®]

Opti-Turn Bench Lathe

300 x 700mm Turning Capacity - 38mm Spindle Bore



Stand Sold Separately

OPTIMUM TU-3008G Opti-Turn Bench Lathe



Right Front View



Front View



Shown with Optional Stand L690 Top View



Shown with Optional Stand L690 Left View



Safety Chuck Guard



Safety Chuck Guard Open Position




Headstock Controls



Spindle Speed Levers and Speed Chart




Headstock Controls



Top View Saddle and Chuck



Spindle Direction and Emergency Stop Switches




On Off Switch



38mm Through Spindle Bore



4 Way Toolpost




Saddle Left View




Saddle Front View


OPTIMUM TU-3008G Opti-Turn Bench Lathe




Saddle Right View




Saddle Rear View




Safety Cutter Guard Left




Safety Cutter Guard Right




Safety Cutter Guard Tilted Down



Feed and Thread Engagement Levers



Swivel Compound Slide



Thread Chasing Dial



Saddle Handwheel Graduations



Compound Slide Hand Wheel



Cross Feed Hand Wheel Graduations



Tailstock



Tailstock Quill Graduations



Tailstock Horizontal Adjustment



Tailstock Hand Wheel




Ground and Hardened Bed


OPTIMUM TU-3008G Opti-Turn Bench Lathe



Change Gears



Slides Ready For Mounting of DRO Scales



Mounting Point for Optional Milling Head



Parts Included

Description

This new TU-3008G model geared head lathe of very modern design has many convenient facilities ideal for the enthusiastic model engineer for small component manufacturer. A very rigid 180mm cast iron bed width, induction hardened and ground slideways gives a high level of precision turning. The lathe capacity is 700mm between the centres and 300mm swing over the bed and with a generous 38mm spindle bore allowing larger stock to be placed through the headstock. The workhorse that drives this lathe has an upgraded powerful 2hp (1.5kW) motor providing smooth running.

Other very useful features included are cross and longitudinal power feeds that's not normally found of small conventional lathes, quick lock tailstock and both metric and imperial thread cutting, ranging from 8-56 tpi or 0.2-3.5mm pitch. Also included are a 4-way indexing tool post with 16mm tool shank capacity, fine adjustment on the tailstock for taper turning and the rear splash guard. A 160mm 3-jaw chuck with reverse jaws is also supplied. There are many additional options available including a milling head (BF-16AV) or (BF-20AV) to turn this machine into a very capable all round machining centre.

Features

- Geared headstock for quick change of 12 spindle speeds 125-2400rpm
- Ribbed prism bed made of grey cast iron
- Inductively hardened and ground bed guideways
- Automatic cross & longitudinal power feeds
- Spindle nose accuracy 0.009mm
- 3 Jaw chuck running accuracy 0.04mm
- D1-4 camlock spindle for quick chuck changes
- Forward & reverse spindle direction switch
- Oils sight glass on head-stock & gearbox
- Change gears for metric and imperial thread cutting
- Enclosed feed and threading gearbox
- Belt cover with tamper proof safety micro switch
- Heavy duty rotating safety chuck guard with micro switch
- Sliding tool post safety guard
- Cross slide & bed length are designed to fit Optimum DRO scales



OPTIMUM TU-3008G Opti-Turn Bench Lathe

Includes

- Change gears for metric & Imperial thread cutting
- Chuck guard
- Toolpost guard
- 2 dead centres
- 3-jaw chuck with reversible jaws
- Swarf drip tray
- Rear splash guard

Specifications

ORDER CODE	L691
MODEL	TU-3008G
Swing Over Bed (mm)	300
Distance Between Centres (mm)	700
Spindle Bore (mm)	38
Swing In Gap (mm)	~
Swing Over Cross-slide (mm)	190
Digital Readout System Fitted	Optional
Quick Change Toolpost Fitted	Optional
Leadscrew Covers Fitted	~
Taper Turning Attachment	~
Coolant System	~
Tool Height To Suit (mm)	16
Centre Height (mm)	150
Spindle Nose Size or Type	D1-4
Bed Width (mm)	180
Headstock Spindle Taper (MT)	5
Tailstock Taper (MT)	3
Cross Slide Travel (mm)	150
Compound Slide Travel (mm)	65
Leadscrew Type	Metric
Metric Cross Feed (X-Axis) (mm/rev)	0.01 ~0.10
Imperial Cross Feed (X-Axis) (inch/rev)	~
Metric Longitudinal Feed (Z-Axis) (mm/rev)	0.085 - 0.83
Imperial Longitudinal Feed (Z-Axis) (inch/rev)	~
Metric Thread Steps & Pitch (No. / mm)	18 (0.2 - 3.5)
Imperial Thread Steps & TPI (No. / TPI)	21 (8 - 56")
3 Jaw Chuck Diameter (mm)	160
4 Jaw Chuck Diameter (mm)	Optional
Spindle Steps / Speeds (No. / rpm)	12 (125 - 2400)
Motor Power (kW / hp)	1.5 / 2
Voltage / Amperage (V / amp)	240 / 10
Shipping Dimensions (L x W x H) (cm)	153 x 71 x 58
Nett Weight (kg)	280