SHAW MACHINERY

12 FILMER ST CLONTARF QLD 4019

Ph: 0738832731 Fx: 0738832732 E: sales@shawmachinery.com.au



P192A Punching Machine PM-35T















Code: P192A Model: PM-35T Capacity: 35T Weight (Nett): 1240

Dimensions: 109 x 82 x 177

Description

Special designed hydraulic cylinder enables the machine to retract faster, also makes our cylinder slimmer, which brings a better appearance to the machine.

Ranging from 35 to 200 tonnes of punching capacities, combined with different throat depths to choose, provides a complete range of models to meet the customer's different requirements.

All optional tooling used on the punching station of S/SD ironworkers can also be used on the PM models, turning the punching machine into an universal machine.

Also Available

- CNC Models with features like:
- Hydraulic material clamping
- Auto datum point
- Transfer ball table
- MODELS AVAILABLE 35T TO 200T

Taiwanese Punching machine

Features

- Specially designed hydraulic circuit system provides high performance, efficiency and accuracy
- Throat depth of 310mm, 510mm, or 760mm
- C-type rigid frame structure
- A 2-hole overhang die holder and a 2-piece gauging table are provided as standard equipment
- Complete range of optional attachments



Includes

- 2 Year Warranty

Specifications

Code	P192A
Model	PM-35T
Punching Pressure	35T
Punch Capacity	Ø18 x 14mm
Diameter X Thickness	Ø50 x 5mm
Channel Flange Punching (h)	180mm
Throat Depth	310mm
Maximum Stroke Length	100mm
Cycle/min (20mm Stroke)	41

Table Size	700 x 500mm
Table Working Height	1050mm
Motor	5HP
Voltage	415V
Weight (nett)	1200kg

