SHAW MACHINERY

12 FILMER STREET

4019 Ph: 0738832731 Fx: 0738832732 E: sales@shawmachinery.com.au

D176 Geared Head Drill GHD-30V





Code:D176Model:GHD-30VCapacity:31.5mm Drilling Capacity withWeight (Nett):368Dimensions:Actor@actic2fl@ed & Tapping

Features

- 31.5mm drill capacity with 125mm spindle travel
- Geared head drilling machine with low, medium, & high selector
- Variable speed from 50-2850rpm with digital display
- Automatic start drill function for repetition work
- Automatic Power Feed with range of (0.06, 0.09, 0.12mm/rev)
- Thread tapping with auto reverse
- Digital readout depth gauge mounted on front panel
- Adjustable accurate depth setting for increased productivity
- Chuck guard with safety micro-switch
- Drill ejector incorporated in machine
- Work light mounted in convenient location
- T slotted work table & base
- Rack & pinion wind-up table
- Square work table tilts to $\pm 45^{\circ}$ & rotates 360°
- Coolant pump system with flexible hose
- 2.2kW / 3hp motor 240V
- Includes 16mm keyless drill chuck and arbor

Includes

- Coolant pump system
- 16mm keyless drill chuck and arbor
- Safety chuck guard



Specifications

CODE	D176
Model	GHD-30V
Drilling Capacity	31.5mm
Thread Tapping Capacity	M20
Spindle Taper	ЗМТ
Spindle Travel	125mm
Throat Depth	285mm
Quill Diameter	62mm
Column Diameter	115mm
Spindle To Table	790mm
Spindle To Base	1270mm
Table Type	Rectangle
Table Size	426 x 400mm
T-Slot Size	14mm

Automatic Quill Feed	0.06, 0.09, 0.12mm/rev
Automatic Quill Feed	~
Work Light	Yes
Coolant System	Yes
Spindle Speed Steps	3 (Variable)
Spindle Speed Range	50-2850rpm
Motor Power	2.2kW / 3hp
Voltage	240V - 15amp
Full Height	1940mm
Weight (Nett)	368kg

