

# P196 Punching Machine PM-80LT





### Description

Special designed hydraulic cylinder enables the machine to retract faster, also makes our cylinder slimmer, which brings a better appearance to the machine.

Ranging from 35 to 200 tonnes of punching capacities, combined with different throat depths to choose, provides a complete range of models to meet the customer's different requirements.

All optional tooling used on the punching station of S/SD ironworkers can also be used on the PM models, turning the punching machine into an universal machine.

### Also Available

- CNC Models with features like:
- Hydraulic material clamping
- Auto datum point
- Transfer ball table
- MODELS AVAILABLE 35T TO 200T

Taiwanese Punching machine

#### Features

- Specially designed hydraulic circuit system provides high performance, efficiency and accuracy
- Throat depth of 310mm, 510mm, or 760mm
- C-type rigid frame structure
- A 2-hole overhang die holder and a 2-piece gauging table are provided as standard equipment
- Complete range of optional attachments



## Includes

- 2 Year Warranty

# Specifications

Code	P196
Model	PM-80LT
Punching Pressure	80T
Punch Capacity	Ø25 x 23mm
Diameter X Thickness	Ø50 x 12mm
Channel Flange Punching (h)	180mm
Throat Depth	510mm
Maximum Stroke Length	100mm
Cycle/min (20mm Stroke)	28

Table Size	700 x 700mm
Table Working Height	1050mm
Motor	7.5HP
Voltage	415V
Weight (nett)	2100kg

