

D165 Radial Arm Drill RAD-900



Code: D165
Model: RAD-900
Capacity: 38mm Drilling Capacity
Weight (Nett): 1270
Dimensions: 157 x 81.2 x 205.7

Features

- Precision Taiwanese manufactured radial drilling machines
- 4-way joystick control for motorised arm rise/fall & forward/reverse spindle direction
- 3 Speed auto down-feed: 0.05, 0.09, 0.15(mm/rev)
- Coolant pump system with flexible hose
- Amp meter providing direct reading of spindle load during operation
- Work light mounted underneath arm providing direct light on work piece
- Heavy duty tee-slotted work table
- Oil-bath lubricated gear drive
- Micro down feed hand wheel for quill
- Safety micro switch located at end of arm
- Wear strip on arm ensuring greater wear resistance whilst maintaining head rigidity
- Quiet and smooth operation
- Reliability - sold for over 20 years

Specifications

CODE	D165	Automatic Quill Feed	0.05, 0.09, 0.15mm/rev
Model	RAD-900	Work Light	Yes
Drill Capacity	38mm	Coolant System	Yes
Threading Capacity	M20	Spindle Speed Steps	6
Spindle Taper	4MT	Spindle Speed Range	88-1500rpm
Spindle Travel	200mm	Motor Power	1.5kW / 2hp
Quill Diameter	70mm	Motor Voltage	415V
Spindle To Column (min-max)	290-920mm	Dimensions (LxWxH)	155 x 85 x 205cm
Spindle To Box Table (max)	785mm	Weight (Nett)	1270kg
Spindle To Base (max)	1110mm		
Table Type	Square		
Box Table Size (LxWxH)	550 x 405 x 315mm		
T-slot Size	20mm		